



W W W . M O T O L I N O . C H

| Engine | 4-valve 4-stroke single cylinder, electronic injection, catalysed |
|--------------------------------------|--|
| Displacement | 124.7 cc |
| Bore x stroke | 52 mm x 58,7 mm |
| Max Power at the crank shaft | 9 kW - 12.2 HP at 8,250 rpm |
| Max Torque | 11.1 Nm at 6,750 rpm |
| Consumption | 41.6 km/l |
| CO ₂ emissions compliance | 60 g/km (61 g/km) |
| Fuel system | Electronic Injection |
| Cooling | Liquid |
| Starter | Electric Start & Stop system |
| Gearbox | CVT automatic with torque server |
| Clutch | Automatic dry centrifugal with shock absorbers |
| Load-bearing structure | Sheet steel shell with welded structural reinforcements |
| Front suspension | Single arm with helical spring and hydraulic shock absorber |
| Rear suspension | Double hydraulic shock absorber with helical spring with preload adjustable in 4 positions |
| Front brake | Stainless steel Ø 220 mm disc with hydraulic control |
| Rear brake | Stainless steel Ø 220 mm disc with hydraulic control |
| ABS/ASR system | ABS standard |
| Front tyre | Tubeless 120/70 - 12" |
| Rear tyre | Tubeless 130/70 - 12" |
| Length/Width/Wheelbase | 1,950 / 755 / 1,380 mm |
| Seat Height | 790 mm |
| Fuel tank capacity | 7 litres |
| Emissions compliance | Euro 4 |